



Exemplary illustration
The Type 4.5 has four instead of six
LED modules

LED recessed light suitable for all common ceiling systems. Frame coated in ceiling colour.

Design with unique LED reflector system and highly efficient all-round glare-free wide-beam light technology (UGR<19). Specially designed for use with high ceilings and/or higher light intensities.

The narrow installed height of 55 mm saves a lot of space.

Seamless closed-cell seal between housing and frame.

Inspection by opening retaining knob.

Туре	Lighting system	Approx. size W x L x H*	
CP 625 ( <u>600</u> ) LED-U3 4.5 AG	LED 840, 4530 Lm, ca. 31W	625x625x55 mm ( <u>600x600x55</u> )	
CP 625 ( <u>600</u> ) LED-U3 6.5 AG	LED 840, 6800 Lm, ca. 47W	625x625x55 mm ( <u>600x600x55</u> )	
CP 625 ( <u>600</u> ) LED-U3 7.5 AG	LED 840, 7860 Lm, ca. 55W	625x625x55 mm ( <u>600x600x55</u> )	
CP 1200x300 LED-U3 6.5 AG	LED 840, 6800 Lm, ca. 47W	1200x300x55 mm	
		*plus cable connection	

## Technical Data:

Voltage: 220-240 V / 50-60 Hz

Protection class: 1

Protection rating: IP65, IP50 on back side

Control unit: switchable, optional DALI dimmer Elec. connection: internal 3-pin plug (DALI 5-pin)

with straight wiring option


Colour: RAL 9016 / customer choice

Glass: toughened safety glass

## Scale diagram:



## Light distribution curve:





## Options:

- emergency light
- elec. connection according to customer requirement
- operable from above (TOP type)

CP LED-U3	LTA-IWS	Page 1 of 1	Rev.02	27.03.2024
-----------	---------	-------------	--------	------------