



Surface-mounted LED tear-drop light for installation directly on ceiling grid.

Diffuse enclosure made of PMMA in streamlined tear-drop shape to prevent air turbulence.

The light can be supplied for separate mounting and for rows of lights.


Inspection: no tools needed. Installation by integral stainless steel springs.

Type	Lighting system	Approx. size W x L x H
TD-L 600 1.5 OA	LED 840, 1590 Lumen, ca. 14 Watt	50 x 600 x 90 mm
TD-L 900 2.0 OA	LED 840, 2350 Lumen, ca. 21 Watt	50 x 900 x 90 mm
TD-L 1200 3.0 OA	LED 840, 3190 Lumen, ca. 28 Watt	50 x 1200 x 90 mm
TD-L 1500 3.5 OA	LED 840, 3980 Lumen, ca. 34 Watt	50 x 1500 x 90 mm

Technical Data:

- Voltage: 220-240 V / 50-60 Hz
- Protection class: 1
- Protection rating: IP40
- Control unit: switchable, optional DALI dimmer
- elec. connection: internal 3-pin plug (DALI 5-pin) with straight wiring option
- Colour: RAL 9016 / customer choice
- Enclosure: diffuse PMMA profile cover

Light distribution curve:



Scale diagram:



Options:

- emergency light
- IP54 (max. two length light-band possible)
- yellow light
- straight wiring
- elec. connection according to customer requirement

Subject to technical changes also without notification. This document is the intellectual property of ourselves. Without our approval, it may not be either reproduced or commercialised, distributed or presented to other individuals for commercial purposes without authorisation to do so.