

Direct and indirect lighting luminaire, equipped with LED technology.

Direct Light is distributed via a microprismatic diffusor, suitable for monitor workstations.

Manufacturing is made on a project-related basis, lengths and light output can be adjusted to requirements.

Delivery inclusive suspension accessories.



Type	Lumen Output	System Power	Dimension (l x w x h)
LK 71 1500 4.0 d/i bMPS-b	di 2.000lm / in 2.000lm	38 Watt	1.500 x 71 x 76 mm
LK 71 1500 6.0 d/i bMPS-b	di 2.000lm / in 4.000lm	57 Watt	1.500 x 71 x 76 mm
LK 71 1500 8.0 d/i bMPS-b	di 2.000lm / in 6.000lm	75 Watt	1.500 x 71 x 76 mm
LK 71 1500 10.0 d/i bMPS-b	di 2.000lm / in 8.000lm	97 Watt	1.500 x 71 x 76 mm

Technical Information:

Voltage:	220-240 V / 50-60 Hz
Protection Class:	1
Protection Type:	IP20
Ballast:	switchable
Cover:	microprismatic
Colour:	RAL 9006
Light Colour:	4.000K
CRI:	RA>80

Options:

- Light Colour 3.000K
- Housing Colour acc. to RAL Card
- Ballast DALI dimmable
- Opal cover

Dimension Drawing:

