



Surface / Recessed luminaire for sports halls, equipped with LED technology.

Housing is made of sheet steel, colour acc. to RAL 9016.

Light is distributed via a clear and ballproof polycarbonate cover. Its ballproof characteristics are certified by DIN 18032 and EN 13964, class 1A.

Acc. to project requirements the luminaire can also be produced for linear light strips.

Type	Lumen Output	System Power	Dimension (l x w x h)
SHL 298 1200 10.5 KS BWS	10.550 Lumen	80 Watt	1.200 x 298 x 95 mm
SHL 298 1200 13.5 KS BWS	13.780 Lumen	104 Watt	1.200 x 298 x 95 mm
SHL 298 1500 13.0 KS BWS	13.180 Lumen	100 Watt	1.500 x 298 x 95 mm
SHL 298 1500 17.0 KS BWS	17.220 Lumen	130 Watt	1.500 x 298 x 95 mm

Technical Information:

Voltage:	220-240 V / 50-60 Hz
Protection Class:	1
Protection Type:	IP40
Ballast:	switchable
Cover:	clear polycarbonate, ballproof
Colour:	RAL 9016
Light Colour:	4.000K
CRI:	RA>80

Options:

- Light Colour 3.000K
- Ballast DALI dimmable
- Housing acc. to RAL Card

Dimension Drawing:

