
# **Lindner**

# T30 / El30 Fire protection door GTB-ADS 80 FR 30



#### **Dimensions**

#### Frame external dimensions

Element width (single leaf) 620 up to 1418 mm Element width (double leaf) 1160 up to 2168 mm Element height 1728 up to 2500 mm

#### System description

Our T30/El30 Fire protection door GTB-ADS 80 FR30 consists of a fire protection door element with a aluminium frame. The system got a glass filling with flush- mountly stuck panes on both sides, and is available as triple glazing in single leaf or double leaf performance.

## **Installation options**

Lindner partition systems



#### Technichal data

Thickness of the door leaf 100 mm

Weight of the door leaf approx. 70 - 80 kg/m2

Front of the door frame; front side 55 mm Front of the door frame; back side 80 mm Profile width of the door leaf; 98 mm

circumferential

Bonding according to ETAG 002 in Structural-Glazing-Process



#### Fire protection

**DIN 4102** T30-1 / T30-2 EI 30 C5 / EI<sub>2</sub> 30 C5

DIN EN 13501-2



#### **Smoke control**

**DIN 18095** RS S<sub>200</sub> DIN EN 13501-2



## Sound insulation

ISO 717-1 o up to 42 dB Rw (=laboratory value)



#### Standard equipment

Roll door-hinge stainless steel

Mortise lock for tube framed door leaves; Class 3;

prepared for profile and round cylinders

Automatically lowerable soil liner

Fitted door closer

Door handles both-sided cropped



# Accessories / options

Integrated door closer

Fitting combinations for emergency exit doors and panic devices

Access control

Supervision contact

etc. depending on the requirement and customer

# Surfaces of the profiles

- E6/C0 anodised aluminium
- o Powder- coated aluminium in RAL- and NCS-colours

#### Glass design

- · Clear glass
- · Low iron glass

#### **Door frame**

• Aluminium door frame

### Information on Lindner Group







and its related logo, is a trendmark owned by the U.S. Green Building Council ®

Customised, project-specific solutions possible

standard o optional

Further information can be found on our homepage www.Lindner-Group.com

