



Dimensions

Door leaf width (1 door leaf)	500 mm up to 1200 mm
Door leaf height	up to 2500 mm

System description

Door leaf made of tubular aluminum frame mitred all round, with safety glass panes glued on both sides as double glazing in a 1- or 2-leaf version. Folding geometry butt-closing with two folds.

Installation options

Solid wall
Plasterboard partitions
Lindner partition systems



Technical data

Thickness of the door leaf	100 mm
Weight of the door leaf	approx. 47 - 57 kg/m ²
Profile width of the door leaf circumferential	91 mm



Sound insulation

ISO 717-1	single leaf up to 45 dB Rw (=laboratory value)
-----------	---



Standard equipment

Barrel door hinge 160 mm with VX absorption
Mortise lock for a tubular frame door; Class 3; prepared for PZ prepared for profile and round cylinders
Bottom seal, which is automatically lowerable
Door handle, which is offset on both sides
Bonding of the surface in light grey



Additional equipment / Options

Door closers, which are superimposed or integrated
Blinds in double glazing, manually or electrically adjustable
Access control
Monitoring contacts
Bonding of the surface in black or white
etc. according to the demands and the customer requests

Surfaces of the profiles

- E6/ C0 anodised aluminium
- Powder- coated aluminium in RAL- and NCS-colours

Glass design

- Clear glass
- Low iron glass

Door frame

- Aluminium door frame
- Steel door frame

Information on Lindner Group



and its related logo, is a trademark owned

by the U.S. Green Building Council ©

Specific solutions are project- related possibly

- standard
- optional

Further information can be found on our homepage www.Lindner-Group.com

